General Specifications for HUH2-20" Fan Size Hydronic Unit Heater

Notes 1. Pressure/Temperature Ratings

Pressure = 400 psig (2758 kPa) Temperature = 550°F (288°C) MDMT = - 20° F (-29° C)

2. Materials

Cabinet: 14 Ga, Yellow Epoxy/Polyester Powder Coated Core: Carbon Steel with Copper-free Aluminum Fins Louvers: Anodized Extruded Aluminum

3. Fluid Connections

2 in, FNPT

Optional Thread-on 2 in. MNPT (shipped loose) Optional 2 in. FNPT CL300# flange (shipped loose)

4. Mounting

5/8 in. - 11 UNC diameter holes on top (4 places)

5. Fan

Spark-proof three-blade aluminum


6. Fan Guard

Split design with close wire spacing. A 3/8 in. (9.5 mm) diameter probe will not enter

7. Ex-Proof Motors

Class I, Divisions 1 & 2, Groups C & D Class II, Divisions 1 & 2, Groups F & G Temperature Code T3B

- ♦ Thread-on fittings. Shipped loose and must be installed on site. C3 connection also includes C2 connection.
- † Standard Marathon NEMA ex-proof motor is suitable for Class I & II, Div. 1 & 2, Groups C, D, F & G; T3B. Ensure equipment meets the requirements of your hazardous location.
- * Other voltages/frequencies available upon request. Longer lead times may apply. Contact factory.
- ▶ NEMA motors are designed to be operated at rated voltage with tolerances of ± 10%. If the motor is marked 208-230V the tolerance must be calculated from 230V. If motor is marked 230V it is still suitable for 208V operation but the tolerance must be calculated from 230V. For 3-phase motors the line-to-line full load voltage must be balanced within 1%.



 Motor Type		
G	General purpose	
Ε [†]	Hazardous Location	

Options

Heresite coated core & cabinet

Connection, 2" FNPT CL300# flange

Special build (Factory assigned code)

Connection, 2" MNPT fitting

Heresite coated core

Heresite coated cabinet

Option Codes

H1, C3, etc.

H1

H2

НЗ


C3◊

Includes louvers & fan blade

Includes louvers & fan blade

Special Requirements/Notes:

The fan shroud is made of spark resistant aluminum compliant to AMCA 99-10, Type B



Fan Size Dim.	20 Inches (mm)	Note: Inlet and Outlet coupling connection locations can be reversed in the field by rotating the core.	
Α	19.49 (495)		
В	4.02 (102)	Mounting Holes, 5/8" 11 UNC (4 places)	
С	2.40 (61)		∏ G
D	24.29 (617)	- L max	
E	10.51 (267)	E	
F	5.75 (146)	-BK max	- Н
G	2.50 (63.5)		♦ Hazloc Heaters
н	3.62 (92)	· •	
I	25.96 (659)	• •	
J	17.00 (432)	I I	<u></u>
K	1.38 (35)		
L	22.57 (573)		
М	30.48 (774)		
	Op	tandard 2" FNPT tional 2" MNPT ional 2" 300# RF	Cecto based witness your search 100
			- M

- P			

Approval Drawing	HUH2-20" Fan Size Heater	
June 7, 2021	Version 1.1	
Hazloc Heaters Inc.	Calgary, Alberta	

